

## Plasticizer Free 100% Solids Non-Slump Moisture Cure Sealant

For Professional Use Only

### DESCRIPTION

- One Component 100% solids, Plasticizer-Free, paintable Hybrid Silicone-Urethane Sealant
- NS: No Slump technology for vertical and overhead applications.
- Plasticizer free formulation, prevents residue formation on surface in lower temperature applications.
- No plasticizer also means product will retain its initial flexibility for the many times longer.
- Designed for Industrial uses requiring elasticity, high strength, and excellent adhesion.
- May be applied to ice- free surfaces at or below freezing temperatures
- Performance at temperatures as low as -40 degrees F.
- Even bonds to damp or wet surfaces and is rain tolerant during cure.
- Cures to a Waterproof tough flexible sealant.
- Low odor and minimal shrinkage.
- Non-staining and mildew resistant.
- UV resistant.
- Very low VOC

### RECOMMENDED USES

Industrial uses requiring high elasticity, high-strength and outstanding adhesion for a wide-range of substrates Everest NS bonds aggressively to steel, aluminum, ceramics, spray foam, Styrofoam, EPS, glass, wood, fiberglass, concrete and coated metals.

Property	Result
<b>Tensile Strength:</b>	<b>300 psi</b>
<b>Elongation at break:</b>	<b>300%</b>
<b>Hardness Shore A</b>	<b>32 (5 day ambient cure)</b>
<b>Application Temperature</b>	<b>13 to 200 Degrees F.</b>
<b>Density</b>	<b>10.5 lbs/gal</b>
<b>Low Temp Flex</b>	<b>-20° F</b>
<b>Service Temp</b>	<b>-40°F to 200°F</b>
<b>Shelf Life (when stored @ 40°F to 80°F)</b>	<b>12 months</b>

### COLORS

White and Gray

### APPLICATION

Can be applied to most surfaces without primer.

### PACKAGING/SHIPPING INFORMATION

#### CONTAINER SIZE

10.3 and 28 fl. oz.  
2 Gallon pail (7.6 liters)

#### SHIPPING CLASS

Class 55  
Class 55

To the best of our knowledge all technical data contained herein is true and accurate as of the date of issuance and subject to change without prior notice. Used must contact Everest systems Company to verify correctness before specifying or ordering. We guarantee our products to conform to the quality control standards established by Everest Systems Products. We assume no responsibility for coverage, performance or injuries resulting from use. Liability if any, is limited to replacement of the product. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY EVEREST SYSTEMS EXPRESSED OR IMPLIED; STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.