

100% Solids Self Leveling Moisture Cure Sealant

For Professional Use Only

DESCRIPTION

- Self-Leveling technology for all seams, fasteners, ridge caps, flashings, and penetrations.
- Moisture Curing multi-purpose one-component sealant/adhesive
- Designed for Industrial uses requiring elasticity, high strength, and excellent adhesion.
- May be applied to surfaces at or below freezing temperatures. Make all attempts to remove frost.
- Performance at temperatures as low as -40 degrees F.
- Bonds to damp surfaces and is rain tolerant during cure.
- Cures to a Waterproof tough flexible sealant.
- Low odor and minimal shrinkage.
- Non-staining and mildew resistant.
- UV resistant.
- VOC Compliant.

RECOMMENDED USES

Industrial uses requiring high elasticity, high-strength and outstanding adhesion for a wide-range of substrates EverSeal bonds aggressively to PVC, aged TPO, metal, steel, aluminum, ceramics, spray foam, Styrofoam, EPS, glass, wood, fiberglass, concrete and coated metals. Contact your local sales representative for specific applications. Always perform a pull test to ensure proper adhesion.

Property	Result
Tensile Strength:	200 psi
Elongation at break:	500%
Hardness Shore A	25 (5 day ambient cure)
Slump	Zero Slump
Application Temperature	13 to 200 Degrees F.
Low Temp Flex	-20° F
Service Temp	-40°F to 200°F
Shelf Life (when stored @ 40°F to 80°F)	12 months

APPLICATION

Can be applied to most surfaces without primer.

COLORS

Tan, Light Gray

PACKAGING/SHIPPING INFORMATION

<u>CONTAINER SIZE</u>	<u>SHIPPING CLASS</u>
10.3 and 28 fl. oz.	Class 55
2 Gallon pail (7.6 liters)	Class 55

To the best of our knowledge all technical data contained herein is true and accurate as of the date of issuance and subject to change without prior notice. Used must contact Everest systems Company to verify correctness before specifying or ordering. We guarantee our products to conform to the quality control standards established by Everest Systems Products. We assume no responsibility for coverage, performance or injuries resulting from use. Liability if any, is limited to replacement of the product. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY EVEREST SYSTEMS EXPRESSED OR IMPLIED; STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

EVEREST SYSTEMS LLC • 1926 Rankin Rd. #110 • Houston, TX 77073

www.EVERESTSYSTEMSCO.com • Phone 800-575-8966